








TUBI CARBURANTE IN GOMMA TRECCIA INTERNA

CODICE	 mm	 mm	 bar	 bar	 bar	 gr/mt	 mm
CARB4X9/20MT	4	9	10	30	-	70	40
CARB5X12/20MT	5	12	10	30	-	124	50
CARB6X12/20MT	6	12	10	30	-	113	60
CARB8X15/20MT	8	15	10	30	-	169	80
CARB10X17/20MT	10	17	10	30	-	198	100
CARB13X20/20MT	13	20	10	30	-	244	130
CARB15X23/20MT	15	23	10	30	-	321	150
CARB19X27/20MT	19	27	10	30	-	389	190
CARB25X35/20MT	25	35	10	30	-	630	250



STRUTTURA BODY

A Sottostrato Tube	Liscio in gomma NBR di colore nero resistente ad oli e carburanti con contenuto di aromatici fino al 40%. Natural and synthetic black rubber.
B Inserti Reinforcement	Tessili sintetici. High tensile synthetic textile.
C Copertura Cover	Liscia in gomma NBR resistente ad oli e carburanti. Oil and Diesel resistant smooth synthetic rubber.
Superficie Surface	Liscia. Smooth.

NORME NORMS:

ISO 1307

MARCATURA MARKING:

EUROCORD® OIL RUBBER HOSE P.E. 10 BAR - ISO 1307

CONFEZIONAMENTO BOX:

IMBALLO IN POLIETILENE ROSSO PACKAGING IN RED POLYETHYLENE

-35°C / +70°C
-31°F / +158°F